

# FEP RTD WIRE

---

## Duplex Unshielded

### PRODUCT DESCRIPTION

<b>Conductor</b>	Stranded
<b>AWG Sizes</b>	#16 AWG - #26 AWG
<b>Insulation / Jacket Type</b>	Fluorinated Ethylene Propylene (FEP ) 200C
<b>Color Code</b>	2C (Red / White) / Jacket (White)
<b>Conductor Material</b>	Silver Plated Copper
<b>Shield Type</b>	Unshielded / Duplex
<b>Approvals</b>	Rohs / Reach Compliant
<b>Applications</b>	Resistance Temperature Detectors / Thermometers / Sensors
<b>Physical Properties</b>	Excellent resistance to abrasion, oil, moisture , acid and low smoke

Part#	Conductor	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692D	16/19	.006"	.085" x .150"	21.8	200C	n/a
R1892D	18/19	.006"	.079" x .138"	17.5	200C	n/a
R2072D	20/7	.006"	.070" x .120"	12.3	200C	n/a
R2272D	22/7	.006"	.062" x .104"	8.5	200C	n/a
R2472D	24/7	.006"	.056" x .092"	6.3	200C	n/a
R2672D	26/7	.006"	.051" x .082"	4.6	200C	n/a