

# ETFE (UL) AWM 1671

---

## 300V 150C

### PRODUCT DESCRIPTION

<b>Conductor</b>	Solid or Stranded Tinned Copper*
<b>AWG Sizes</b>	#30 AWG - #10 AWG
<b>Insulation Type</b>	(ETFE) - 12 solid colors + striping available
<b>Approvals</b>	(UL) AWM Style 1671 300V 150C RoHS Compliant
<b>Applications</b>	Internal wiring of appliances, electrical heaters, thermocouple, more
<b>Physical Properties</b>	Excellent resistance to gasoline, oil, moisture and acid

Part#	Conductor	Insulation Thickness	Overall Diameter			
8610-1671	10/37	.010"	.127"	31	300V	150C
8612-1671	12/19	.010"	.109"	23	300V	150C
8614-1671	14/19	.010"	.090"	15	300V	150C
8616-1671	16/19	.010"	.073"	9	300V	150C
8618-1671	18/19	.010"	.067"	7	300V	150C
8621-1671	20/7	.010"	.058"	5	300V	150C
8623-1671	22/7	.010"	.050"	3	300V	150C
8625-1671	24/7	.010"	.044"	2.2	300V	150C
8627-1671	26/7	.010"	.039"	1.5	300V	150C
8629-1671	28/7	.010"	.035"	1.1	300V	150C
8630-1671	30/7	.010"	.032"	0.9	300V	150C

\* Additional strandings are available