



Aerospace Part#: SFJ183 **CONTROL CABLE**

DESCRIPTION

3 Conductors AWG 18/19x30 SPC

Overall SPC Braid Shield Type E Inners M16878/4 TFE/FEP White 600V

PHYSICAL PROPERTIES

Conductors			Insulation		
# Conductors	AWG	Material	Material	Wall	Finished OD
3	18/19x30	Silver Plated Copper	TFE	.011"	.069"

Outer Braid Material

Layer 1 Type	AWG	Coverage	
Overall SPC Copper Braid	36	85%	

Cabling **Outer Jacket Material Jacket Material** Color Wall Overall O.D. Lay FEP White .015" .201" Nom. 2" Lay on Cable

MECHANICAL PROPERTIES

	Operating Temp	Total Weight	Bend Radius	
	Rated -65C to 200C	42.3 lbs / m	10 X OD	

ELECTRICAL PROPERTIES

Max. Operating Voltage		
Rated 600 Volts		

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES	
Suitability	Direct Burial, Wet Location	
Resistance	Oil, Gas, Sunlight, Abrasian, Acid	

MISCELLANEOUS

Color Black / Red / White /

Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} Specification subject to error and may change without notice