



Aerospace Part#: **SFJ202 CONTROL CABLE** 

## **DESCRIPTION**

2 Conductors AWG 20/19x32 SPC

Overall SPC Braid Shield Type E Inners M16878/4 TFE/FEP White 600V

### **PHYSICAL PROPERTIES**

onductors Insulation					
# Conductors	AWG	Material	Material	Wall	Finished OD
2	20/19x32	Silver Plated Copper	TFE	.010"	.058"

**Outer Braid Material** 

Layer 1 Type	AWG	Coverage
Overall SPC Copper Braid	36	85%

Cabling **Outer Jacket Material Jacket Material** Color Wall Overall O.D. Lay FEP White .015" .169" Nom. 1.5" Lay on Cable

**MECHANICAL PROPERTIES** 

Operating Temp	Total Weight	Bend Radius	
Rated -80C to 200C	26.0 lbs / m	10 X OD	

#### **ELECTRICAL PROPERTIES**

Max. Operating Voltage	
Rated 600 Volts	

# **INDUSTRY APPROVALS AND COMPLIANCE**

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasian, Acid

## **MISCELLANEOUS**

Color Black / White /

Code:

## **Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

<sup>\*</sup> Specification subject to error and may change without notice