

**Aerospace Part#:** SFJ243

**CONTROL CABLE**

**DESCRIPTION**

3 Conductors AWG 24/19x36 SPC  
Overall SPC Braid Shield Type E Inners M16878/4 TFE/FEP White 600V

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
3	24/19x36	Silver Plated Copper	TFE	.010"	.043"

**Outer Braid Material**

Layer 1 Type	AWG	Coverage
Overall SPC Copper Braid	36	85%

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.015"	.145" Nom.	1" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -65C to 200C	20.1 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 600 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Color: Black / White / Red /  
Code:

**Contact Us For More Information**

**T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com**

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice