



Aerospace Part#: STJ204 CONTROL CABLE

DESCRIPTION

4 Conductors AWG 20/19x32 SPC

Overall SPC Braid Shield Type E Inners M16878/4 TFE/TFE White 600V (B83350E)

PHYSICAL PROPERTIES

Conductors Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
4	20/19x32	Silver Plated Copper	Tetrafluoroethylene (TFE)	.010"	.058"

Outer Braid Material

Layer 1 Type	Material	AWG	Coverage
Overall Braid Shield	Silver Plated Copper	36	85%

Outer Jacket Material Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
TFE Tape Wrapped	White	.012"	.187" Nom.	1.75" Lay on Cable

MECHANICAL PROPERTIES

	Operating Temp	Total Weight	Bend Radius	
I	Rated -80C to 200C	33.0 lbs / m	10 X OD	

ELECTRICAL PROPERTIES

Max. Operating Voltage	
Rated 600 Volts	

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Standards & Environmental Programs		
Reach / RoHS Compliant	YES	
Suitability	Indoor / Outdoor	
Resistance	Oil, Gas, Weather, Abrasian, Acid	
NEMA Compliance	HP3 / WC 55021	
MIL-SPEC Compliance	M16878/4 / MIL-C-55021	

MISCELLANEOUS

Color Code: Black / White / Red / Green /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} Specification subject to error and may change without notice