

Aerospace Part#: STJ243

CONTROL CABLE

**DESCRIPTION**

3 Conductors AWG 24/19x36 SPC  
Overall SPC Braid Shield Type E Inners M16878/4 TFE/TFE White 600V (B83333E)

**PHYSICAL PROPERTIES**

**Conductors**

# Conductors	AWG	Material	Insulation Material	Wall	Finished OD
3	24/19x36	Silver Plated Copper	Tetrafluoroethylene (TFE)	.010"	.043"

**Outer Braid Material**

Layer 1 Type	Material	AWG	Coverage
Overall Braid Shield	Silver Plated Copper	36	85%

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
TFE Tape Wrapped	White	.012"	.139" Nom.	1" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	18.1 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 600 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Indoor / Outdoor
Resistance	Oil, Gas, Weather, Abrasion, Acid
NEMA Compliance	HP3 / WC 55021
MIL-SPEC Compliance	M16878/4 / MIL-C-55021

**MISCELLANEOUS**

Color Code: Black / White / Red /

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

\* Specification subject to error and may change without notice