

Aerospace Part #: TC106F

600V 200C FEP Cable

DESCRIPTION

6 Conductors AWG 10 / 37x26 TPC shielded FEP / FEP

Applications

- Tray, Audio, Instrumentation, Control
- Resistant to chemical, gas, oil, sunlight, and water

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG / Matl.	Material	Wall / Finished OD	Color Code
6	10 / 37x26 / TPC	FEP	.013" / .136"	Chart 1

Outer Shield Material

Drain Wire

Type of Shield	Material	AWG / Matl.
Overall	Aluminum / Mylar	12 / 19 / TPC

Outer Jacket Material

Cabling

Jacket Matl / Color	Wall	Overall O.D.	Lay on Cable
FEP / Gray	.012"	0.436" nom	6" LHL

MECHANICAL PROPERTIES

Operating Temp	Weight
neg 80C to 200C	229 lb / 1000 ft

ELECTRICAL PROPERTIES

Max. Operating Voltage	Capacitance	VOP
600V	48 pF/ft	69%

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Mil-Spec Standard	M16878/11
RoHS Compliant	YES
Passes Flame Test	UL910/1581-NFPA 262-FT-6-IEEE-383
FDA Code	121.2555
NEMA	HP-4
Suitability	Direct Burial / Tray Applications / F&B Plants

MISCELLANEOUS

[Contact Us For More Information](#)

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUMS RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA