

Aerospace Part #: TC1212F
600V 200C FEP Cable
DESCRIPTION

12 Conductors AWG 12 / 19x.0185" TPC shielded FEP / FEP

Applications

- Tray, Audio, Instrumentation, Control
- Resistant to chemical, gas, oil, sunlight, and water

PHYSICAL PROPERTIES
Conductors
Insulation

| # Conductors | AWG / Matl. | Material | Wall / Finished OD | Color Code |
|--------------|----------------------|----------|--------------------|-------------------------|
| 12 | 12 / 19x.0185" / TPC | FEP | .015" / .117" | Chart 1 |

Outer Shield Material
Drain Wire

| Type of Shield | Material | AWG / Matl. |
|----------------|------------------|---------------|
| Overall | Aluminum / Mylar | 14 / 19 / TPC |

Outer Jacket Material
Cabling

| Jacket Matl / Color | Wall | Overall O.D. | Lay on Cable |
|---------------------|-------|--------------|--------------|
| FEP / Gray | .015" | 0.520" nom | 6" LHL |

MECHANICAL PROPERTIES

| Operating Temp | Weight |
|-----------------|------------------|
| neg 80C to 200C | 306 lb / 1000 ft |

ELECTRICAL PROPERTIES

| Max. Operating Voltage | Capacitance | VOP |
|------------------------|-------------|-----|
| 600V | 35 pF/ft | 69% |

INDUSTRY APPROVALS AND COMPLIANCE
Standards & Environmental Programs

| | |
|-------------------|--|
| Mil-Spec Standard | M16878/11 |
| RoHS Compliant | YES |
| Passes Flame Test | UL910/1581-NFPA 262-FT-6-IEEE-383 |
| FDA Code | 121.2555 |
| NEMA | HP-4 |
| Suitability | Direct Burial / Tray Applications / F&B Plants |

MISCELLANEOUS
Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUMS RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice