

**Aerospace Part #: TC1412F**
**600V 200C FEP Cable**
**DESCRIPTION**

12 Conductors AWG 14 / 19x.0147" TPC shielded FEP / FEP

**Applications**

- Tray, Audio, Instrumentation, Control
- Resistant to chemical, gas, oil, sunlight, and water

**PHYSICAL PROPERTIES**
**Conductors**
**Insulation**

# Conductors	AWG / Matl.	Material	Wall / Finished OD	Color Code
12	14 / 19x.0147" / TPC	FEP	.014" / .098"	<a href="#">Chart 1</a>

**Outer Shield Material**
**Drain Wire**

Type of Shield	Material	AWG / Matl.
Overall	Aluminum / Mylar	16 / 19 / TPC

**Outer Jacket Material**
**Cabling**

Jacket Matl / Color	Wall	Overall O.D.	Lay on Cable
FEP / Gray	.012"	0.435" nom	6" LHL

**MECHANICAL PROPERTIES**

Operating Temp	Weight
neg 80C to 200C	203 lb / 1000 ft

**ELECTRICAL PROPERTIES**

Max. Operating Voltage	Capacitance	VOP
600V	32.4 pF/ft nom	69%

**INDUSTRY APPROVALS AND COMPLIANCE**
**Standards & Environmental Programs**

Mil-Spec Standard	M16878/11
RoHS Compliant	YES
Passes Flame Test	UL910/1581-NFPA 262-FT-6-IEEE-383
FDA Code	121.2555
NEMA	HP-4
Suitability	Direct Burial / Tray Applications / F&B Plants

**MISCELLANEOUS**
**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUMS RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**