



Aerospace Part#: 8700/3 (UL) TYPE Z

DESCRIPTION

1 Conductor AWG 3/o/1665x30 TC UL Type Z Hook Up Wire ETFE

PHYSICAL PROPERTIES

Conductors Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
1	3/o/1665x30	Tinned Copper	ETFE	.045"	.616"

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -65C to 150C*	586.5 lbs/m	10 X OD

ELECTRICAL PROPERTIES

<u>EEEGTRIGAET ROTERTIEG</u>					
Max. Operating Voltage					
UL Rated 600 Volts					

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

NEC / (UL) Specification	UL Type Z
Reach / RoHS Compliant	YES
Suitability	Direct Burial, Radiation
Resistance	Oil, Gas, Sunlight, Abrasian, Acid
Flame Test	VW-1 / UL 1581 / IEEE 383

MISCELLANEOUS

Markings: E161093 3/o AWG ETFE 600V (UL) TYPE Z

Color: TBD

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} The temperature limit is 90C for general use and 150c for special applications.

^{**} Specification subject to error and may change without notice